

A **TATA** Product

VOLTAS



Presenting the new range of All Weather
Water Dispensers from Voltas.



VOLTAS

*all*weather™

Presenting the versatile range of All Weather Water Dispensers from Voltas.

Experience the versatility of water. Hot enough to stimulate you with a cup of tea or coffee and cold enough to refresh you with a glass of pure water or with a soft drink concentrate. A perfect blend of design and efficiency, the new All Weather Water Dispenser is just what every office, home and shop needs. So whatever the weather, you can enjoy your drinks just the way you like.

Water Dispenser - Technical Specifications

Model	Units	Minimagic Pure T	Minimagic Pure R	Minimagic Pure F	Minimagic Pearl F	Minimagic Pearl R
Product Code		6210163	6210164	6210165	6210166	6210167 / 6210169
Type		Table Top	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted
Cabinet Type		NA	Cooling Cabinet	Storage Cabinet	NA	Cooling Cabinet
Power Supply		230 V ~ 50 Hz	230 V ~ 50 Hz	230 V ~ 50 Hz	230 V ~ 50 Hz	230 V ~ 50 Hz
No. of Faucets	Nos.	3	3	3	3	3
Cold Water Storage Capacity	Ltrs	3.2	3.2	3.2	3.2	3.2
Cooling Capacity	Ltrs/Hr	3	2.5	3	3	2.5
Cooling Power Consumption	Watt	80/86	86	80/86	80/86	86
Hot Water Storage Capacity	Ltrs	0.9	0.9	0.9	0.9	0.9
Heating Capacity	Ltrs/Hr	5	5	5	5	5
Heating Power Consumption	Watt	500 +/- 5%	500 +/- 5%	500 +/- 5%	500 +/- 5%	500 +/- 5%
Unit Dimension (W X D X H)	mm	310 x 345 x 490	310 x 345 x 940	310 x 345 x 940	310 x 345 x 490	310 x 345 x 940
Packaged Unit Dimension (W X D X H)	mm	347 x 375 x 540	347 x 375 x 990	347 x 375 x 990	347 x 375 x 540	347 x 375 x 990
Weight (Gross/Net)	Kg	12.8/11.7	18.2/16.5	16.7/15.05	12.8/11.7	18.2/16.5
Refrigerant		Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)
Cabinet Capacity/Refrigerator Capacity	Ltrs	NA	20	20	NA	20
Cooling Cabinet Temperature	°C	NA	≤12°C	NA	NA	≤12°C
Compressor Cooling		Yes	Yes	Yes	Yes	Yes
Function (Hot, Normal & Cold)		Yes	Yes	Yes	Yes	Yes
Display (LED Indicator)		Yes	Yes	Yes	Yes	Yes
Hot Water Dispensing Lock		Yes	Yes	Yes	Yes	Yes

Model	Units	Minimagic Pure FS	Minimagic Super T	Minimagic Super R	Minimagic Super F	Minimagic Plus T
Product Code		6210171	6210174	6210173	6210175	6210177
Type		Floor Mounted	Table Top	Floor Mounted	Floor Mounted	Table Top
Cabinet Type		NA	NA	Cooling Cabinet	Storage Cabinet	NA
Power Supply		230 V ~ 50 Hz	230 V ~ 50 Hz	230 V ~ 50 Hz	230 V ~ 50 Hz	230 V ~ 50 Hz
No. of Faucets	Nos.	3	3	3	3	3
Cold Water Storage Capacity	Ltrs	3.2	3.2	3.2	3.2	3.2
Cooling Capacity	Ltrs/Hr	3	3	2.5	3	3
Cooling Power Consumption	Watt	80/86	80/86	86	80/86	80/86
Hot Water Storage Capacity	Ltrs	0.9	0.9	0.9	0.9	0.9
Heating Capacity	Ltrs/Hr	5	5	5	5	5
Heating Power Consumption	Watt	500 +/- 5%	500 +/- 5%	500 +/- 5%	500 +/- 5%	500 +/- 5%
Unit Dimension (W X D X H)	mm	310 x 345 x 940	325x380x555	325x380x1000	325x360x1000	325x400x570
Packaged Unit Dimension (W X D X H)	mm	347 x 375 x 990	347x405x575	347x405x1025	347x405x1025	347x405x575
Weight (Gross/Net)	Kg	16.7/15.05	11.4/12.9	16.5/18.4	16.3/18	11.4/12.9
Refrigerant		Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)
Cabinet Capacity/Refrigerator Capacity	Ltrs	NA	N/A	19/20	19/20	N/A
Cooling Cabinet Temperature	°C	NA	NA	≤12°C	NA	NA
Compressor Cooling		Yes	Yes	Yes	Yes	Yes
Function (Hot, Normal & Cold)		Yes	Yes	Yes	Yes	Yes
Display (LED Indicator)		Yes	Yes	Yes	Yes	Yes
Hot Water Dispensing Lock		Yes	Yes	Yes	Yes	Yes

Model	Units	Minimagic Plus R	Minimagic Plus F	Minimagic Wave T	Minimagic Wave R	Minimagic Wave F
Product Code		6210176	6210178	6210180	6210179	6210181
Type		Floor Mounted	Floor Mounted	Table Top	Floor Mounted	Floor Mounted
Cabinet Type		Cooling Cabinet	Storage Cabinet	NA	Cooling Cabinet	Storage Cabinet
Power Supply		230 V ~ 50 Hz	230 V ~ 50 Hz	230 V ~ 50 Hz	230 V ~ 50 Hz	230 V ~ 50 Hz
No. of Faucets	Nos.	3	3	3	3	3
Cold Water Storage Capacity	Ltrs	3.2	3.2	3.2	3.2	3.2
Cooling Capacity	Ltrs/Hr	2.5	3	3	2.5	3
Cooling Power Consumption	Watt	86	80/86	80/86	86	80/86
Hot Water Storage Capacity	Ltrs	0.9	0.9	0.9	0.9	0.9
Heating Capacity	Ltrs/Hr	5	5	5	5	5
Heating Power Consumption	Watt	500 +/- 5%	500 +/- 5%	500 +/- 5%	500 +/- 5%	500 +/- 5%
Unit Dimension (W X D X H)	mm	325x400x1020	325x380x1020	310x345x490	310x345x940	310x345x940
Packaged Unit Dimension (W X D X H)	mm	347x405x1025	347x405x1025	347x375x540	347x375x990	347x375x990
Weight (Gross/Net)	Kg	16.7/18.7	16.3/18.2	11.4/12.9	16.65/18.65	15.5/17.35
Refrigerant		Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)
Cabinet Capacity/Refrigerator Capacity	Ltrs	19/20	19/20	N/A	19/20	19/20
Cooling Cabinet Temperature	°C	≤12°C	NA	NA	≤12°C	NA
Compressor Cooling		Yes	Yes	Yes	Yes	Yes
Function (Hot, Normal & Cold)		Yes	Yes	Yes	Yes	Yes
Display (LED Indicator)		Yes	Yes	Yes	Yes	Yes
Hot Water Dispensing Lock		Yes	Yes	Yes	Yes	Yes

As a continuing policy of product innovation at VOLTAS, the design and specifications are subject to change without prior notice. The visuals of the product shown overleaf are representative only. Actual product might differ from the one shown.

Voltas 24x7 Customer Service - 1800 425 4555 (Toll Free) or SMS <AC> to 56677. www.voltasac.com

CORPORATE HEAD OFFICE: Voltas Ltd, A-43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi - 110044. Phone: 011 66505550. **BRANCHES:** **DELHI:** Voltas Ltd, A-43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi - 110044. Phone: 011-66505552. **GHAZIABAD:** Voltas Ltd., D-15, R.S. Plaza, 3rd Floor, Raj Nagar, RDC, Ghaziabad - 201001, Ph. 0120 6404801. **CHANDIGARH:** Voltas Ltd, SCO NO. 201-203, 2nd Floor Sector 34A, Chandigarh, Phone: 0172 6610116/17/20. **LUCKNOW:** Voltas Limited, Shalimar Titanium, Block-C, 4th floor, Office Nos. 410 - 412, Plot No. TCG -1/1, Opp. Indira Gandhi Pratishthan, Vibhuti Khand, Gomti Nagar, Lucknow - 226 010, Phone: 0522-6566961. **JAIPUR:** Voltas Ltd, Diamond Tower, 201-203, Purani Chungi, Ajmer Road, Jaipur-302017, Phone: 0141-6451747/48. **HYDERABAD:** Voltas Ltd, 7-2-1735, Sanath Nagar, Hyderabad-500018. Phone: 040-66743001. **BANGALORE:** Voltas Ltd, 7th Floor, 701- Pride Hulkul 116, Labbagh Road, Bangalore- 560027, Phone: 08022535600. **CHENNAI:** Voltas Ltd, No. 264, Anna Salai, Chennai - 600018, Phone: 66760333/11. **KOCHI:** Voltas Ltd, Ambanath building, 39/3522, M.G. Road, Ravipuram, Kochi-682016, Phone: 0484-6605555. **COIMBATORE:** Voltas Ltd, 1413, Trichy Road, Coimbatore - 641018, Phone: 0422-6502419/6530080. **MUMBAI:** Voltas Ltd, Voltas House B, 2nd Floor, T.B. Kadam Marg, Chinchpokli, Mumbai - 400033, Phone: 022-66656333. **PUNE:** Voltas Ltd, Equitorial Forum, 2nd & 3rd Floor, Mumbai-Pune Road, Wakadewadi, Pune-411003, Phone: 020-66011776. **THANE:** Voltas Ltd, Unit II, 1st Floor, 2nd Pokhran Road, Thane-400601, Phone: 022-67920106/07. **AHMEDABAD:** Voltas Ltd, A-301, Shivalik Corporate Park, Shivrangini Crossroad Satellite, Ahmedabad- 380015, Phone: 0790-66301190/91. **INDORE:** Voltas Ltd, The View, 305, Y.N. Road, 3rd Floor, South Tukoganj Thana, Indore-452001, Phone: 0731-4046393/4043512. **KOLKATA:** Voltas Ltd., Unit No.805, 8th Floor, Godrej Waterside Tower-2, Plot No. - 5, Block DP, Sector - V, Salt Lake, Kolkata - 700091, Phone: 033-66266207. For Institutional Inquiry - 09163362409. **PATNA:** Voltas Ltd, Maharaaja Complex, 306-A, 3rd Floor, Frazer Road, Patna-800001, Phone: 0612-3222555/6455192. For Institutional Inquiry - 09431104056. **JAMSHEDPUR:** Voltas House, 3rd Floor, Main Road, Bistupur, Jamshedpur - 831001, Phone: 0657-6455921. For Institutional Inquiry - 09771491152. **BHUBANESWAR:** Voltas Ltd, B-15, 2nd Floor, Arihant Plaza, Shaheed Nagar, Bhubaneswar-751007, Phone: 0674-2544919/18. For Institutional Inquiry - 09937140010. **RAIPUR:** Voltas Ltd, Kunwar Ben Karsam Bhai Chamber, Shop No. 419/420, 4th Floor, New Timber Market, Mandi Market, Devendra Nagar Raipur - 492001, Ph: 4033886.

Voltas Ltd. adheres to the E-Waste (Management & Handling) Rules 2011 notified by the Ministry of Environment and Forests, Government of India. For more information on Voltas E-Waste and exchange policy please contact 1800-419-3283.